



Installing HP-UX 9.10 and Y2K patches on the HP 382 from TAMS CDs.

Insert the HP-UX 9.10 "Install Disk" into CD ROM Drive.

Power on the 382 and press the space bar until the system beeps (attended boot)

Choose: II SYSINSTALL from system directory:

press: II <Enter>

The screen will eventually say "Welcome to HP-UX Install. There are basically 4 steps to installing HP-UX (etc.)"

<Press any key to continue>

The system will load a default file system. It will eventually ask you to verify if the correct hard drive is selected. Verify and press the correct selection # (usually option 1 will be highlighted)

"Do you want the root file system to allow long file names?"

If yes, press: y

The installation will continue and every now and then ask if you really want to continue...

"Verify that the root disk swap space is sufficient." You don't have to change the default value, but you can if you want.

press: CTRL-X to accept the defaults

"Continuing will destroy the contents of the disk listed above. Do you wish to continue?"

press: y

The system will install for a few minutes. Eventually it will prompt you with the following:

"Ensure that the install media unit has been removed and an update media unit is online and prepared for reading."

Remove the "Install Disk" from the CD ROM Drive, and insert the "Core Software" Disk.

press Enter to continue

When prompted, choose "Select all filesets on the source media."

press Enter (you'll then see: "--working--")

When prompted, choose "Start loading now."

press Enter (you'll then see: "--calculating disk space requirements--")

After a minute or so, you'll see, " Because the KERN-BLD fileset was chosen, and more than one license...(etc)."

Choose option 1, "02-USER".

"The update should complete without additional attention...(etc)."

"Start loading filesets now?" (y or n)

press y

The system will then perform the installation. It takes about 35 minutes for it to complete this phase.

Installing "Y2K Patches"

Insert the CD called "Y2K Patches" into the drive.

At the "#" prompt, mount the CD containing the Y2K patches.

```
Mount /dev/dsk/cEd2s0 /UPDATE_CDROM
```

(Note: This example specifies SCSI ID 2. Change the 2 in cEd2s0 to specify your source drive SCSI address)

The following command will install the patches

```
Update -r -s /UPDATE_CDROM '*'
```

The system will reboot. Remove the Y2K patches disc from the CD ROM Drive

You must then login again.

Installing "Additional Y2K Patches"

Insert the CD called "Additional Y2K Patches" into the drive.

Mount the CD with the following command:

```
mount /dev/dsk/cEd2s0 /UPDATE_CDROM
```

Run the update with the following command to install the additional patches:

```
Update -r -s /UPDATE_CDROM/PHCO_16850.updt PHCO_16850
```

You are now finished installing HP-UX 9.10 and the Y2K patches